

SINGLE PHASE - DESIGN
HEAT EXCHANGER: B10THx10/1P

SWEP DThermX

Date: 30/06/2025

SSP Alias: B10T

DUTY REQUIREMENTS

		Side 1	Side 2
Fluid		Propylene Glycol - Water (20.0 mass%)	Water
		Counter-Current	
Flow type		Outer	Inner
Circuit			
Heat load	kW	7.000	
Inlet temperature	°C	80.0	50.0
Outlet temperature	°C	60.0	70.0
Flow rate	kg/s	0.08570	0.08362
Pressure drop (Design PD)	kPa	1.35 (20.00)	1.84 (20.00)
Thermal length		2.00	2.00

PLATE HEAT EXCHANGER

		Side 1	Side 2
Total heat transfer area	m ²		0.248
Heat flux	kW/m ²		28.2
Mean temperature difference	K		10.0
Overall heat transfer coefficient required	W/m ² ;°C		2820
Pressure drop - total*	kPa	1.35	1.84
- in ports	kPa	0.0171	0.0164
Port diameter (up/down)	mm	24.0/24.0	24.0/24.0
Number of channels per pass		5	4
Number of plates			10
Oversurfacing	%		4
Fouling factor	m ² ;°C/kW		0.012
Reynolds number		468.5	792.7
Port velocity (up/down)	m/s	0.191/0.191	0.188/0.188
Channel velocity	m/s	0.0763	0.0941
Shear stress	kPa	5.48e-3	7.49e-3
Average wall temperature	°C	64.7	64.2
Largest wall temperature difference	K		1.5
Min./Max. wall temperature	°C	55.2/75.2	53.7/73.7

*Excluding pressure drop in connections.

PHYSICAL PROPERTIES

		Side 1	Side 2
Reference temperature	°C	70.0	60.0
Dynamic viscosity	cP	0.648	0.467
Density	kg/m ³	994.1	983.2
Heat capacity	kJ/kg;°C	4.084	4.185
Thermal conductivity	W/m;°C	0.5351	0.6544
Film coefficient	W/m ² ;°C	6110	7850

TOTALS


		Side 1	Side 2
Total weight empty (no connections)*	kg	2.11 - 3.06	
Total weight filled (no connections)*	kg	2.65 - 3.6	
Hold-up volume (Inner Circuit)	dm ³	0.24	
Hold-up volume (Outer Circuit)	dm ³	0.3	
Port size F1/P1	mm	24	
Port size F2/P2	mm	24	
Port size F3/P3	mm	24	
Port size F4/P4	mm	24	

*Weight depends on the selected product.

DIMENSIONS



DIMENSIONS



A	mm	289 ±2
B	mm	119 ±1
C	mm	243 ±1
D	mm	72 ±1
E	mm	20 (opt. 45) ±1
F*	mm	26.4 - 30.4 +0.5%/-1.5%
G*	mm	4 - 6 ±1
R*	mm	22 - 23

*Dimensions depend on the selected product.

*This is a schematic sketch. For correct drawings please use the order drawing function or contact your SWEP representative.

CARBON FOOTPRINT

	Unit	Value
Sweden - Landskrona	kg CO ₂ e	10.9 - 15.8
USA - Tulsa	kg CO ₂ e	11.4 - 16.5
Slovakia - Košice	kg CO ₂ e	12.4 - 17.9
Malaysia - Kuala Lumpur	kg CO ₂ e	17.2 - 25.0
China - Suzhou	kg CO ₂ e	29.6 - 42.8

Legal notice:

By using the SSP/DThermX software the Licensee confirms that the input data is not subject to export control laws including ITAR (International Traffic in Arms Regulations). Licensee further agrees and confirms that the configured products are not subject to export control laws including ITAR and do not qualify as "specially designed" for export control purposes. If you would like to discuss configuration of export controlled products including ITAR-qualifying products, or if your data is export controlled, please reach out to your SWEP representative or email info@swepgroup.com.

Disclaimer:

Data used in this calculation is subject to change without notice. SWEP strives to use "best practice" for the calculations leading to the above results. Calculation is intended to show thermal and hydraulic performance, no consideration has been taken to mechanical strength of the product. Product restrictions - such as pressure, temperatures and corrosion resistance- can be found in SWEP product sheets and other technical documentation. SWEP may have patents, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from SWEP, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property. To the maximum extent permitted by applicable law, the software, the calculations and the results are provided without warranties of any kind, whether express or implied. No advice or information obtained through use of the software (including information provided in the results), will create any warranty not expressly stated in the applicable license terms. Without limiting the foregoing, SWEP does not warrant that the content (including the calculations and the results) is accurate, reliable or correct. SWEP does not warrant that any system comprising heat exchanger and other components, installed on the basis of calculations in this software, will meet your requirements or function to your satisfaction or expectations.

